



AN ISO 9001:2008 CERTIFIED COMPANY

AN EYE THAT NEVER SLEEPS....

2MEGA PIXEL BULLET NETWORK CAMERA

MODEL: TI-QX4-BIR-IP2000



KEY FEATURES:

TECHNOLOGY DATA

Sensor	1/2.8" Progressive Scan CMOS or better
Resolution	Full HD 1920(H)x1080(V) 50 and 60 Hz
Signal System	PAL/NTSC
Minimum Illumination	Color : 0.05 lux at F1.4, 1/30 sec or better B/W : 0.01 lux at F1.4, 1/30 sec or better and 0.002 with IR
White Balance	Auto/Manual/ATW/Indoor/Outdoor/Daylight lamp/Sodium lamp

**Product casing and specification are subject to change without any prior notice*

www.tentronix.in; info@tentronix.in



	with AGC, BLC, HLC WDR Support
Shutter Time	1/3 s to 1/100,000 s
Focal Length	4 mm F 2.0 or better
IR irradiation distance	50mtrs
Alarm	Line Crossing, Intrusion Detection, Motion detection, Dynamic analysis, Tampering alarm, Network disconnect ,IP address conflict, Storage exception
Alarm Input /Output	min 2 output and 1 input
Audio Input/Output	1 x in and out both
Network	10Base -T, /100Base-TX, RJ45 Connector
Compression	H.264 / MJPEG
Protocols	IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, S NMP, DNS, DDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE
Simultaneous Users	min 15 No
Streaming	Dual streaming support
Memory Card	Support up to 128GB Micro SD/SDHC/SDXC card.
User Level	Up to 24 users,3 Levels: Administrator, Operator and User
Security	Password Access, Privacy mask
Features	Date and Time Smart detection: intrusion detection, line crossing detection, audio exception detection Smart recording: edge recording, support smart search in smart NVR
Power	AC Adapter, POE 802.3af
Power Consumption:	Max. 7W
Working Temperature	-30 to +60 degree
Compliance	IP66
Compliance	ISO 9001:2008, ONVIF,Fcc,Rohs,CE

**Product casing and specification are subject to change without any prior notice*

www.tentronix.in; info@tentronix.in

