

AN EYE THAT NEVER SLEEPS....

2 MP 36X NETWORK IR PTZ DOME CAMERA

MODEL: TI-QX4-PTZ-IP-2036X

KEY FEATURES:

- 1/2.8" Type solid State Progressive Scan CCD, up to 1920X1080
- Smart IR, 150m IR distance
- True Day/Night, 3D DNR
- WDR
- 36X Optical Zoom
- IP66 rating
- HLC/BLC



SPECIFICATIONS:

TI-QX4-PTZ-IP-2033X	
IMAGES SENSOR	1/2.8" PROGRESSIVE SCAN CMOS
EFFECTIVE PIXEL	1920(H)X1080(V)
SIGNAL SYSTEM	PAL/NTSC
MINIMUM ILLUMINATION	COLOR:0.1LUX@(F1.6,AGC ON) B/W:0.01 LUX@(F1.6,AGC ON) 0LUX WITH IR
WHITE BALANCE	AUTO/MANNUAL
S/N RATIO	>= 50D
DIGITAL NOISE REDUCTION	3D DNR
WIDE DYNAMIC RANGE	WDR
ELECTRONIC SHUTTER SPEED	AUTO/ MANUAL, 1/3~1/10000S

**Product casing and specification are subject to change without any prior notice*

DAY & NIGHT	AUTO ICR/ COLOR/ B-W
BLACK LIGHT COMPENSATION	HLC/BLC
WHITE BALANCE	AUTO/ATW
GAIN CONTROL	AUTO/ MANUAL
NOISE REDUCTION	3D
PRIVACY MASKING	N/A
LENS	
FOCAL LENGTH	4.7-84.6MM ,36X
DIGITAL ZOOM	SUPPORTED
MAX APERTURE	F1.6
ANGLE OF VIEW	59.7-3.6 DEGREE (WIDE TELE)
APERTURE RANGE	F1.6-F2.8
NETWORK	
ETHERNET	RJ-45(10/100BASE-T)
PROTOCOL	TCP/IP , UDP , RTP , RTSP , RTCP , HTTP , DNS , DDNS , DHCP , FTP , NTP , PPPOE , SMTP UPNP
COMPATIBILITY	ONVIF
MAX. USER ACCESS	10 USERS
SMART PHONE	ANDROID , IPHONE
PRESET	256
GENERAL	
POWER SUPPLY	DC 12V
POWER CONSUMPTION	< 6W
WORKING ENVIRONMENT	-10°C~+60°C, 10%~90%
INGRESS PROTECTION	IP66
DIMENSION	30*30*37(CM)
PACKAGE WEIGHT	7 KG
APPROVALS	CE FCC ROHS

AN ISO 9001:2008 CERTIFIED COMPANY

For enquiry: www.tentronix.in

info@tentronix.in

**Product casing and specification are subject to change without any prior notice*

